


UNIVERSAL PRODUCT LINE

SERIES: 8124A, 8123A, 8127A

CAST IRON, STEEL EXTERNALS & STAINLESS STEEL

FEATURES & BENEFITS

- Sealless mag drive eliminates the shaft seal to provide the highest level of liquid and vapor containment
- All liquid and vapor is hermetically sealed in the pump
- Used especially for hazardous and difficult-to-seal liquids



Stepped housing keeps the outer magnet from contacting the canister in the unlikely event of bearing failure

The inner magnet is the driven magnet, aligned by magnetic force passing through the canister; the inner magnet assembly is shielded in a laser welded 316SS housing to prevent exposure of the magnets to the liquid

The outer magnet is the drive magnet, driven directly by the motor

Canister & Bushing Assembly

Thrust Washers

Multiple port sizes, types and ratings are available including threaded and flanged

Adjustable Internal relief valve standard, optional return-to-tank and jacketed available

Rotor Idler

Rotatable pump casing in 90° increments, permitting four different port positions. Opposite ports casings also available.

One-piece cast bracket provides rigid foundation that is dimensionally interchangeable with Universal Product Line pumps

Adaptor Plate

VIKING PUMP®



CAPACITY

to 500 GPM
(114 m³/h)



PRESSURE

to 200 PSI
(14 BAR)



TEMPERATURE

-120°F to +500°F
(-85°C to +260°C)



VISCOSITY

28 to 250,000 SSU
(0.1 to 55,000 cSt)




PERFORMANCE

MODELS			SPECIFICATIONS				
Sealless Mag Drive			Performance			Standard Ports	
Cast Iron	Steel Externals	Stainless Steel	Max Speed, RPM	GPM	m ³ /h	Size, Inches	Type
H8124A	H8123A	H8127A	1750	15	3.5	1.5	NPT*
HL8124A	HL8123A	HL8127A	1750	30	7	1.5	NPT*
K8124A	K8123A	K8127A	780	80	18	2	NPT*
KK8124A	KK8123A	KK8127A	780	100	23	2	NPT*
L8124A	—	—	640	135	31	2	NPT
LQ8124A	LQ8123A	LQ8127A	640	135	31	2.5	Flange
LL8124A	LL8123A	LL8127A	640	170	39	3	Flange
LS8124A	LS8123A	LS8127A	640	200	45	3	Flange
Q8124A	Q8123A	Q8127A	520	300	68	4	Flange
QS8124A	QS8123A	QS8127A	520	500	114	6	Flange

* 8123A and 8127A models standard with flanged ports

CURVES



PORTING

- Right Angle (90°) (Rotatable Casing), H-Q
- Opposite (180°) (Rotatable Casing), QS
- NPT / BSP
- Flanged (ANSI Compatible)

SEALING

- Sealless Mag Drive

MOUNTING

- Foot Mount

DRIVES

- Ⓡ Offset Gear Reducer Drive
- Ⓟ Purchased Gear Reducer Drive
- ⓓ Direct-Mounted Drive

TYPICAL APPLICATIONS

- Petrochemicals
- Isocyanates
- Polyols
- Monomers
- Resins
- Adhesives
- Sodium Hydroxide
- Paints & Coatings
- Solvents
- Petroleum & Additives
- Biofuels
- Oil Seeds

VIKING PUMP®

VIKING PUMP, INC.

A Unit of IDEX Corporation
406 State Street
Cedar Falls, Iowa 50613 U.S.A.
vikingpump.com

Contact Your Stocking Distributor Today

Distributed By: AUSTRALIAN DISTRIBUTOR



KelairPumps

CALL 1300 789 466

When Pump Knowledge Matters
www.kelairpumps.com.au

United States
vikingpump.com

Cedar Falls, Iowa
Phone: (319) 266-1741

Canada
vikingpumpcanada.com

Windsor, Ontario
Phone: (519) 256-5438

Europe & Africa
vikingpump.com

Shannon, Ireland
Phone: +353 (61) 471933

Asia-Pacific
idexfmi-asia.com

China - Shanghai
Phone: +86-21-5241-5599
India - Mumbai
Phone: +91-22-6643-5563
Singapore
Phone: +65-6684-7305

Middle East
vikingpump.com

Dubai, UAE
Phone: +971 4 2600300

Latin America
vikingpump.com

Australia & New Zealand
vikingpump.com

